



~ NOTES ~

ALL INTEGRAL CURBS SHOWING REINFORCING STEEL SHALL BE CAST SEPARATELY FROM THE PAVEMENT AND THE REINFORCEMENT SHALL CONSIST SOLELY OF NO. 4 BARS AS DETAILED ON THIS DRAWING. ON CONSTRUCTION CARE SHOULD BE TAKEN SO THAT NO REINFORCEMENT BARS ARE CLOSER THAN 3" TO THE CENTER OF THE SAWED TRANSVERSE JOINT.

①② THE CONTRACTOR HAS THE OPTION OF CONSTRUCTING THE STANDARD INTEGRAL CURB AS DETAILED IN EITHER ① OR ②. IF ② IS CHOSEN A LONGITUDINAL CONSTRUCTION JOINT SHALL BE REQUIRED AND THE REMAINING PAVEMENT AND CURB SHALL BE CONSTRUCTED MONOLITHIC WITHOUT A HORIZONTAL CONSTRUCTION JOINT AND ACCOMPANYING REINFORCING STEEL.

KENTUCKY
DEPARTMENT OF HIGHWAYS

CURB AND GUTTER,
CURBS AND
VALLEY GUTTER

STANDARD DRAWING NO. RPM-100-09

SUBMITTED: *Sam W. Stone* 12-2-02
DIRECTOR DIVISION OF DESIGN DATE

APPROVED: *J. M. Yocum* 12-2-02
STATE HIGHWAY ENGINEER DATE